

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
17 March 2005 (17.03.2005)


PCT

(10) International Publication Number  
**WO 2005/024987 A2**

- (51) International Patent Classification<sup>7</sup>: **H01M 8/06**
- (21) International Application Number: **PCT/JP2004/012033**
- (22) International Filing Date: 16 August 2004 (16.08.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
2003-314283 5 September 2003 (05.09.2003) JP
- (71) Applicant (for all designated States except US): **NISSAN MOTOR CO., LTD.** [JP/JP]; 2, Takara-cho, Kanagawa-ku, Yokohama-shi, Kanagawa, 2210023 (JP).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **HASHIGAYA, Hiroaki** [JP/JP]; 3-51-1, Noukendai, Kanazawa-ku, Yokohama-shi, Kanagawa, 2360057 (JP). **SUZUKI, Kelsuke** [JP/JP]; 2-13-8, Honfujisawa, Fujisawa-shi, Kanagawa, 2510875 (JP). **KAMIHARA, Tetsuya** [JP/JP]; 2-39-5-202, Miyamoto-cho, Minami-ku, Yokohama-shi, Kanagawa, 2320016 (JP).
- (74) Agent: **GOTO, Masaki**; Shoyu-Kaikan 3-1, Kasumigaseki 3-chome, Chiyoda-ku, Tokyo, 1000013 (JP).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: FUEL CELL SYSTEM



(57) Abstract: A fuel cell stack (1) comprises a reactive gas passage (115, 1c, 116, 1a) and a water passage (117, 1b) substantially parallel thereto, and a reactive gas is humidified by water permeating from the water passage (117, 1b) through a porous member (112a, 112c). The pressure reduction amounts in the reactive gas passage (115, 1c, 116, 1a) and the water passage (117, 1b) are respectively calculated based on the power generation load of the stack (1). From the pressure reduction amounts in the water passage (117, 1b) and the reactive gas passage (115, 1c, 116, 1a), the pressure of the reactive gas supplied to the reactive gas passage (115, 1c, 116, 1a) is controlled such that the difference in pressure between the reactive gas passage (115, 1c, 116, 1a) and the water passage (117, 1b) is within a predetermined range, whereby the reactive gas is humidified in a desirable state.



---

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*